


Concrete Vehicle Wheel Stop Barrier

Rationale	Permanent vehicle wheel stop barrier for car parks etc. to keep vehicles within specific areas and to protect surrounding property.
Application	Vehicle wheel stop barrier for indoors or outdoors.
Detail	<ul style="list-style-type: none"> • Measurement: 1650 x 155 x 100mm • Steel reinforced • Impact resistant and durable. • Will not rust or rot. • Slots on underside allow drainage and for lifting. • Holes for mounting bolts, bolt hole recessed • Strength of concrete shall be in excess of 20MPa • Cement shall be type GP, general purpose Portland cement or similar, complying with the requirements of NZS 3122 • Can be coloured to any Paving Worx, Perma Colour or Peter Fell colours. • Designed to meet standard AS/NZS 2890.1:2004, latest standard covering Wheel Stops
Cost	Please contact Paving Worx Ltd for details



not to scale



Nb. FOR INSTALLATION OF CONCRETE WHEEL STOPS A MORTAR, GROUT OR EPOXY TYPE BEDDING COMPOUND IS REQUIRED TO TAKE UP DIMENSIONAL TOLLERANCES BETWEEN PRECAST CONCRETE AND THE SURFACE YOU ARE FIXING TO, PLEASE TAKE EXTRA CARE WITH THE CENTRE FOOTING.

Paving Worx Ltd, 55 Aviation Ave, Mount Maunganui.
(07) 572 1557 | 0800 2 PAVE IT (0800 272 8348)
info@pavingworx.co.nz | www.pavingworx.co.nz